



**HYDROSTATIC
LEVEL TRANSMITTERS**

HYDROSTATIC LEVEL TRANSMITTERS - HLX

APPLICATIONS

Liquid / continuous level measurement:

- Level control in pumping station
- Water treatment
- In a ballast water tank for ship building
- In the sewage sector
- In splash water containers for swimming pools
- In chloride-containing media

BRIEF DESCRIPTION

The level probe is used for the continuous hydrostatic level measurement in ventilated tanks. Measuring is carried out unaffected by electrical medium features or any foam formation.

Approvals are needed for particular ship building requirements and explosion protection.

The level probe can be readily used in depths from as low as 1 mWs and has been designed for application in liquids with media containing chlorides. These may be found in ship building, swimming pools, or water and sewage water management.

The surrounding pressure is compensated for using a cable with an integrated pressure equalization hose. The cost-optimized titanium level probe with a front-flush membrane offers an alternative in highly viscous media. The screwable protective cap protects the membrane.

The level probe is equipped with a reverse-polarity protection mechanism which prevents incorrect polarity during startup.

Another benefit to the measuring system is the extensive range of accessories for an optimum design.

CUSTOMER BENEFITS

- Improved plant availability
- Standardized signal processing
- Resistant to climate due to improved moisture and vibration protection
- Measurements in very harsh and highly viscous media thanks to the front-flush membrane
- Prevention of build up of resistance
- A complete solution for measurement points thanks to the extensive range of accessories
- Reverse-polarity protection mechanism

SPECIAL FEATURES

- Highly resistant to chemicals thanks to the titanium version
- Measuring ranges from 100 mbar relative pressure and 600 mbar
- Absolute pressure are available
- Proven piezoresistive silicon sensor
- Approval marks



Hydrostatic Level Transmitters-HLX

TECHNICAL DATA

GENERAL INFORMATION

| | |
|--------------------------|--|
| Reference conditions | According to DIN 16086 and DIN 61298 |
| Measuring principle | Piezoresistive sensor with titanium membrane |
| Pressure transfer medium | Synthetic oil |
| Admissible load changes | >10 million, 0% to 100% measuring range |
| Mounting | Vertical / hanging from the cable |

OUTPUT

| | |
|---|---|
| Analog output Current Output 405 | 4 to 20mA, 2-wire HART & MODBUS(RS485) OPTIONAL |
| Step response t_{90} | 2ms |
| Burden Current 4 to 20 mA, 2-wire | $RL \leq (UB - 16 V) \div 0.022 A (\Omega)$ |

AUXILIARY POWER

| | |
|--|--------------------------------------|
| Voltage supply U_B^a | For basic type DC 16-28V Nominal 24V |
| Reverse voltage protection | Yes |
| Max. current consumption | 23 mA |
| Electrical circuit | SELV |
| The voltage peaks must not exceed the specified voltage supply values! | |

CABLE

| | |
|---|---|
| 6-core, shielded cable with integrated pressure compensation hose, AWG 24 with ferrules | |
| Material | |
| Outer sheath | FEP |
| Compensation hose | PA |
| Color | Black |
| Outer diameter | Approx. 8.4 mm |
| Conductor cross section | 0.25 mm ² |
| Bending radius | |
| Moving | min. 140 mm |
| Fixed | min. 70 mm |
| Tensile force | 4000 N |
| Mass | ≈90 g/m |
| Admissible temperatures | -40 to +70 °C (depending on the medium) |
| UV resistance | Yes, according to DIN ISO 4892-2 |

MECHANICAL FEATURES

Ensure the medium durability of the material

| | |
|----------------------|------------------|
| Material | |
| Protective cap | PVC |
| Process connection | Titanium grade 2 |
| Measuring membranes | Titanium grade 2 |
| Case | Titanium grade 2 |
| Shrink tubing | Polyolefin |
| Mass (without cable) | 109 g |
| Diameter | 27 mm |


ENVIRONMENTAL INFLUENCES

| | | | | | | | | | | | | | | | | | |
|--|---|-------------------|------------------------|----|---------------|----|---------------|----|---------------|-------------------|------------------------|----------|--------------|---------|--------------|---------|--------------|
| Admissible temperatures | | | | | | | | | | | | | | | | | |
| Medium | <p>0 to 50 °C The level probe must not freeze in the medium A restriction may be required depending on the medium.</p> <p>Ignition protection type Gb</p> <table border="1"> <tr> <td>Temperature class</td> <td>Ambient temperature TA</td> </tr> <tr> <td>T4</td> <td>-40 to +85 °C</td> </tr> <tr> <td>T5</td> <td>-40 to +70 °C</td> </tr> <tr> <td>T6</td> <td>-40 to +55 °C</td> </tr> </table> <p>Ignition protection type Db</p> <table border="1"> <tr> <td>Temperature class</td> <td>Ambient temperature TA</td> </tr> <tr> <td>T 100 °C</td> <td>40 to +85 °C</td> </tr> <tr> <td>T 85 °C</td> <td>40 to +70 °C</td> </tr> <tr> <td>T 70 °C</td> <td>40 to +55 °C</td> </tr> </table> | Temperature class | Ambient temperature TA | T4 | -40 to +85 °C | T5 | -40 to +70 °C | T6 | -40 to +55 °C | Temperature class | Ambient temperature TA | T 100 °C | 40 to +85 °C | T 85 °C | 40 to +70 °C | T 70 °C | 40 to +55 °C |
| Temperature class | Ambient temperature TA | | | | | | | | | | | | | | | | |
| T4 | -40 to +85 °C | | | | | | | | | | | | | | | | |
| T5 | -40 to +70 °C | | | | | | | | | | | | | | | | |
| T6 | -40 to +55 °C | | | | | | | | | | | | | | | | |
| Temperature class | Ambient temperature TA | | | | | | | | | | | | | | | | |
| T 100 °C | 40 to +85 °C | | | | | | | | | | | | | | | | |
| T 85 °C | 40 to +70 °C | | | | | | | | | | | | | | | | |
| T 70 °C | 40 to +55 °C | | | | | | | | | | | | | | | | |
| Storage | -20 to +70 °C, dry | | | | | | | | | | | | | | | | |
| Electromagnetic Compatibility ^a Interference emission Interference immunity | Class B ^b Industrial requirements | | | | | | | | | | | | | | | | |
| Protection type ^c | IP68 | | | | | | | | | | | | | | | | |

MEASURING RANGE AND ACCURACY

| Measuring range bar | Linearity ^a % MSP ^d | Accuracy at 20 °C ^c % MSP | 10 to 50 °C ^d % MSP | Long-term stability ^b % MSP per year | Overload capacity bar | Burst pressure bar |
|---|--|--|--------------------------------------|--|-----------------------------|--------------------------|
| 0 | | | | | | |
| 0 bar to 0.1 bar relative pressure | 0.2 | 1.2 | 1.9 | ≤0.4 | 0.3 | 0.4 |
| 0 bar to 0.16 bar relative pressure | 0.2 | 0.8 | 1.8 | | 0.48 | 0.64 |
| 0 bar to 0.25 bar relative pressure | 0.2 | 0.8 | 1.7 | ≤0.3 | 0.75 | 1 |
| 0 bar to 0.4 bar relative pressure | 0.2 | 0.7 | 1.7 | | 1.2 | 1.6 |
| 0 bar to 0.6 bar relative/absolute pressure | 0.2 | 0.7 | 1.6 | ≤0.2 | 1.8 | 2.4 |
| 0 bar to 1 bar relative/absolute pressure | 0.2 | 0.6 | 1.3 | | 3 | 4 |
| 0 bar to 1.6 bar relative/absolute pressure | 0.25 | 0.5 | 1.3 | | 4.8 | 6.4 |
| 0 bar to 2.5 bar relative/absolute pressure | 0.25 | 0.5 | 1.2 | | 7.5 | 10 |
| 0 bar to 4 bar relative/absolute pressure | 0.25 | 0.5 | 1.2 | | 12 | 16 |
| 0 bar to 6 bar relative/absolute pressure | 0.25 | 0.5 | 1.2 | | 18 | 24 |
| 0 bar to 10 bar relative/absolute pressure | 0.25 | 0.5 | 1 | | 30 | 40 |

- ^a Linearity according to limit point setting
- ^b Includes: linearity, hysteresis, repeatability, deviation from measuring range start (offset), and measuring range end
- ^c Includes: linearity, hysteresis, repeatability, deviation from measuring range start (offset) and measuring range end, thermal influences on measuring range start (offset), and measuring span
- ^d MSP = measuring span




DIMENSIONS

L Cable length according to customer preference


(a) Protective cap

(b) 5 bore holes for every $\phi 5\text{mn}$




CABLE CLAMP

Terminal box with pressure compensation



(1) Fastening hole



SEALING SCREW

CONNECTION DIAGRAM

The connection diagram in the data sheet provides preliminary information about the connection options. For the electrical connection, only when the installation instructions or the operating manual. The knowledge and the correct technical compliance with the safety information and warnings contained in these documents are mandatory for mounting, electrical connection, and startup as well as for safety during operation.

| CONNECTION | TERMINAL ASSIGNMENT |
|------------|--|
| |  <p data-bbox="1249 748 1326 779">Cable</p> |

4 to 20 mA, 2-wire


| | | |
|------------------------------|-------------------------------|---------------|
| Rated voltage supply DC 24 V | $U_B/S+^a$ $0\text{ V}/S-$ | White Gray |
|------------------------------|-------------------------------|---------------|

Shielding

| | |
|---|-------|
| Caution: Ground the device! Ground all connected devices (such as pumps and valves) to the same potential! | Black |
|---|-------|

^a The voltage peaks must not exceed or fall below the specified voltage supply values!

CONNECTION EXAMPLE



HQ and Manufacturing - 1

SHRIDHAN Automation Pvt. Ltd.
#B-54, KSSIDC Industrial Estate,
Kumbalgotu, Mysore Road,
Bangalore-560074. India.
Ph no - +91-80-2843 7847 / 7848
Email - info@shridhan.com

Manufacturing - 2

SHRIDHAN Automation Pvt. Ltd.
#D-13 KIADB Industrial Area,
Kumbalgotu, Mysore Road,
Bangalore-560074. India.

Manufacturing - 3

SHRIDHAN Automation Pvt. Ltd.
#D-18, KIADB Industrial Area,
Kumbalgotu, Mysore Road,
Bangalore-560074. India.

Middle East

ORBIT Automation FZE
#Z3-38, II Floor, PO Box - 122828,
SAIF Zone, Sharjah, UAE.
A 100% Subsidiary of
SHRIDHAN Automation Pvt. Ltd., India.
Ph No : +971 6 5792662
Email - me@shridhan.com

Europe

SHRIDHAN Sensortek B.V.
James Wattstraat 6,
5051 DT, Goirle,
The Netherlands.
Ph No: +31 13 304 00 01
Email - europe@shridhan.com

